

REVISION #:6

Material Safety Data Sheet

May be used to comply with OSHA Hazard Communication Standard, 29CFR 1910.1200. Standard must be consulted for specific requirements.

U S Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on Label and List)

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

NU-POWER-II

SECTION I

Manufacturer's Name

Emergency Telephone Number

NUVITE CHEMICAL COMPOUNDS CORP.

800-255-3924 (USA) - 813-248-0585 (INT'L)

Address (Number, Street, City, State and ZIP Code)

Telephone Number for Information:

213 Freeman Street

718-383-8351

Brooklyn, New York 11222

Date Prepared: April 22, 2009

SECTION II - Hazardous ingredients/identity information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
Petroleum Distillate	500 PPM	200 PPM	---	38

No other restricted ingredients as listed by OSHA 29CFR 1910.1000 - 1500 ACGIH, OR EPA 40CFR Part 261.3, 302.4, 355, 370, 372

This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313: NONE

SECTION III - Physical/Chemical Characteristics

Boiling Point: 0F 185 Specific Gravity (H2O = 1): @25 oC 0.96

Vapor Pressure (mm Hg.): @ 20 oC 18 Melting Point: Not Applicable

Vapor Density (AIR = 1): Greater than 1 Evaporation Rate (Butyl Acetate = 1): Less than 1

Solubility in Water: Dispersible

Appearance and Odor: Brown, opaque, semi-viscous liquid - mild odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 142 oF. C.O.C. Flammable Limits: Not Applicable LEL ---- UEL ----

Extinguishing Media: Water spray, foam, dry chemical, CO2

Special Fire Fighting Procedures: Wear full protective safety equipment as standard practice

Unusual Fire and Explosion Hazards: None

Product : NU-POWER-II Revision # : 6 Date: April 22, 2009

Section V - Reactivity Data

Stability	Unstable	Conditions to Avoid
	Stable	X None

Incompatibility (Materials to Avoid): Strong acids, bases, oxidizing agents.

Hazardous Polymerization:	May Occur	Conditions to Avoid
	Will Not Occur	X NONE

Section VI - Health Hazard Data

Routes of Entry: Inhalation: Secondary Skin: Primary Ingestion: Tertiary

Health hazards (Acute and Chronic):

ACUTE : SKIN: May cause irritation and drying on skin; EYES: Will cause moderate irritation upon direct contact. INHALATION: Breathing high concentrations will irritate nose and throat; INGESTION: Aspiration hazard.

CHRONIC: None

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure: May cause redness and irritation to exposed skin areas during prolonged exposure

Medical Conditions Generally Aggravated by Exposure: Workers with skin disorders or sensitivity should avoid contact with this product.

Emergency and First Aid Procedures: SKIN: Flush with soap & water. EYES: Flush with water for 20 minutes and immediately contact

Physician. INHALATION: Administer fresh air or oxygen; INGESTION: DO NOT induce vomiting - Immediately contact physician with urgency.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: Contain all spills. Use inert absorbent material and dispose in proper chemical waste container. Do not introduce material directly into rivers, lakes, streams, etc.

Waste Disposal Method: Dispose in accordance with Federal, State and Local regulations.

Precautions to Be Taken in Handling and Storing: When not in use, keep container closed. Store indoors. Keep from freezing.

Other Precautions: Product becomes slippery when mixed with water. Use caution when walking where product has contacted floor. Dispose of empty drums to re-conditioner.

Section VIII - Control Measures

Respiratory Protection (Specify Type): Should vapors exceed PEL, wear NIOSH approved dust and organic vapor respirator for the removal of dried product (dust) from surface.

Ventilation	Local Exhaust: REQUIRED	Special: NOT APPLICABLE
	Mechanical (General): Adequate to maintain below PEL	Other: Open door/window

Protective Gloves: Recommended if exposure is prolonged - Neoprene

Eye Protection: Goggles recommended when spraying or working on overhead structures or if direct contact evident.

Other Protective Clothing or Equipment: Work clothes, face shield and cap if contact or splashing likely.

Work/Hygienic Practices: Wash thoroughly after use and wash work clothes. Water source in work area recommended.

END

REVISION #:7

Material Safety Data Sheet

May be used to comply with OSHA Hazard Communication Standard, 29CFR 1910.1200. Standard must be consulted for specific requirements.

U S Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on Label and List)

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

NU-POWER-II

SECTION I

Manufacturer's Name

Emergency Telephone Number

NUVITE CHEMICAL COMPOUNDS CORP.

800-255-3924 (USA) - 813-248-0585 (INT'L)

Address (Number, Street, City, State and ZIP Code)

Telephone Number for Information:

213 Freeman Street

718-383-8351

Brooklyn, New York 11222

Date Prepared: October 31, 2011

SECTION II - Hazardous ingredients/identity information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
Petroleum Distillate	500 PPM	200 PPM	---	38

No other restricted ingredients as listed by OSHA 29CFR 1910.1000 - 1500 ACGIH, OR EPA 40CFR Part 261.3, 302.4, 355, 370, 372

This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313: NONE

SECTION III - Physical/Chemical Characteristics

Boiling Point: °F	185	Specific Gravity (H2O = 1): @25 °C	0.96
Vapor Pressure (mm Hg.): @ 20 °C	18	Melting Point:	Not Applicable
Vapor Density (AIR = 1): Greater than	1	Evaporation Rate (Butyl Acetate = 1):	Less than 1
Solubility in Water:	Dispersible		
Appearance and Odor:	Brown, opaque, semi-viscous liquid - mild odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used):	142 °F.	C.O.C.	Flammable Limits: Not Applicable	LEL ----	UEL ----
Extinguishing Media:	Water spray, foam, dry chemical, CO2				
Special Fire Fighting Procedures:	Wear full protective safety equipment as standard practice				
Unusual Fire and Explosion Hazards:	None				

REVISION #: 5

Material Safety Data Sheet

May be used to comply with OSHA Hazard Communication Standard, 29CFR 1910.1200. Standard must be consulted for specific requirements.

U S Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on Label and List)

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

NU-POL

SECTION I

Manufacturer's Name

Emergency Telephone Number

NUVITE CHEMICAL COMPOUNDS CORP.
Address (Number, Street, City, State and ZIP Code)
213 Freeman Street
Brooklyn, New York 11222

800-255-3924 (USA) - 813-248-0585 (INT'L)
Telephone Number for Information:
718-383-8351

Date Prepared: October 31, 2011

SECTION II - Hazardous ingredients/identity information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	% (Optional)
Petroleum Distillate	500 PPM	200 PPM	---	38
Silica (SiO2) (Respirable dust)*	0.1 mg M3	0.1 mg/M3	----	6

* NOTE: SiO2 is embodied in product thus restricting airborne respirable dust.

No other restricted ingredients as listed by OSHA 29CFR 1910.1000 - 1500 ACGIH, OR EPA 40CFR Part 261.3, 302.4, 355, 370, 372

This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313: NONE

NFPA = 2-0-0

SECTION III - Physical/Chemical Characteristics

Boiling Point: °F	185	Specific Gravity (H2O = 1): @25 °C	0.985
Vapor Pressure (mm Hg.): @ 20 °C	18	Melting Point:	Not Applicable
Vapor Density (AIR = 1): Greater than	1	Evaporation Rate (Butyl Acetate = 1): Less than	1
Solubility in Water:	Dispersible		
Appearance and Odor:	White, opaque, semi-viscous liquid - mild odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used):	142 °F. C.O.C.	Flammable Limits: Not Applicable	LEL ----	UEL ----
Extinguishing Media:	Water spray, foam, dry chemical, CO2			
Special Fire Fighting Procedures:	Wear full protective safety equipment as standard practice			
Unusual Fire and Explosion Hazards:	None			

Product : NU-POWER-II Revision # : 7 Date: October 31, 2011

Section V - Reactivity Data

Stability	Unstable	Conditions to Avoid
	Stable X	None

Incompatibility (Materials to Avoid): Strong acids, bases, oxidizing agents.

Hazardous Polymerization:	May Occur	Conditions to Avoid
	Will Not Occur X	NONE

Section VI - Health Hazard Data

Routes of Entry: Inhalation: Secondary Skin: Primary Ingestion: Tertiary

Health hazards (Acute and Chronic):

ACUTE : SKIN: May cause irritation and drying on skin; EYES: Will cause moderate irritation upon direct contact. INHALATION: Breathing high concentrations will irritate nose and throat; INGESTION: Aspiration hazard.

CHRONIC: None

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure: May cause redness and irritation to exposed skin areas during prolonged exposure

Medical Conditions Generally Aggravated by Exposure: Workers with skin disorders or sensitivity should avoid contact with this product.

Emergency and First Aid Procedures: SKIN: Flush with soap & water. EYES: Flush with water for 20 minutes and immediately contact

Physician. INHALATION: Administer fresh air or oxygen; INGESTION: DO NOT induce vomiting - Immediately contact physician with urgency.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: Contain all spills. Use inert absorbent material and dispose in proper chemical waste container. Do not introduce material directly into rivers, lakes, streams, etc.

Waste Disposal Method: Dispose in accordance with Federal, State and Local regulations.

Precautions to Be Taken in Handling and Storing: When not in use, keep container closed. Store indoors. Keep from freezing.

Other Precautions: Product becomes slippery when mixed with water. Use caution when walking where product has contacted floor. Dispose of empty drums to re-conditioner.

Section VIII - Control Measures

Respiratory Protection (Specify Type): Should vapors exceed PEL, wear NIOSH approved dust and organic vapor respirator for the removal of dried product (dust) from surface.

Ventilation	Local Exhaust: REQUIRED	Special: NOT APPLICABLE
	Mechanical (General): Adequate to maintain below PEL	Other: Open door/window

Protective Gloves: Recommended if exposure is prolonged - Neoprene

Eye Protection: Goggles recommended when spraying or working on overhead structures or if direct contact evident.

Other Protective Clothing or Equipment: Work clothes, face shield and cap if contact or splashing likely.

Work/Hygienic Practices: Wash thoroughly after use and wash work clothes. Water source in work area recommended.

END

REVISION #:7

Material Safety Data Sheet

May be used to comply with OSHA Hazard Communication Standard, 29CFR 1910.1200. Standard must be consulted for specific requirements.

U S Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on Label and List)

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

NU-POWER-II

SECTION I

Manufacturer's Name	Emergency Telephone Number
NUVITE CHEMICAL COMPOUNDS CORP.	800-255-3924 (USA) - 813-248-0585 (INT'L)
Address (Number, Street, City, State and ZIP Code)	Telephone Number for Information:
213 Freeman Street	718-383-8351
Brooklyn, New York 11222	

Date Prepared: October 31, 2011

SECTION II - Hazardous ingredients/identity information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	% (Optical)
Petroleum Distillate	500 PPM	200 PPM	---	38

No other restricted ingredients as listed by OSHA 29CFR 1910.1000 - 1500 ACGIH, OR EPA 40CFR Part 261.3, 302.4, 355, 370, 372

This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313: NONE

SECTION III - Physical/Chemical Characteristics

Boiling Point: °F	185	Specific Gravity (H2O = 1): @25 °C	0.96
Vapor Pressure (mm Hg.): @ 20 °C	18	Melting Point:	Not Applicable
Vapor Density (AIR = 1): Greater than	1	Evaporation Rate (Butyl Acetate = 1): Less than	1
Solubility in Water:	Dispersible		
Appearance and Odor:	Brown, opaque, semi-viscous liquid - mild odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 142 °F. C.O.C. Flammable Limits: Not Applicable LEL ---- UEL ----

Extinguishing Media: Water spray, foam, dry chemical, CO2

Special Fire Fighting Procedures: Wear full protective safety equipment as standard practice

Unusual Fire and Explosion Hazards: None

-2-

Product: NU-POWER-II Revision #: 7 Date: October 31, 2011**Section V - Reactivity Data**

Stability	Unstable	Conditions to Avoid
	Stable X	None

Incompatibility (Materials to Avoid): Strong acids, bases, oxidizing agents.

Hazardous Polymerization:	May Occur	Conditions to Avoid
	Will Not Occur X	NONE

Section VI - Health Hazard Data**Routes of Entry:** Inhalation: Secondary Skin: Primary Ingestion: Tertiary**Health Hazards (Acute and Chronic):**

ACUTE : SKIN: May cause irritation and drying on skin; EYES: Will cause moderate irritation upon direct contact. INHALATION: Breathing high concentrations will irritate nose and throat; INGESTION: Aspiration hazard.

CHRONIC: None

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure: May cause redness and irritation to exposed skin areas during prolonged exposure**Medical Conditions Generally Aggravated by Exposure:** Workers with skin disorders or sensitivity should avoid contact with this product.**Emergency and First Aid Procedures:** SKIN: Flush with soap & water. EYES: Flush with water for 20 minutes and immediately contact**Physician:** INHALATION: Administer fresh air or oxygen; INGESTION: DO NOT induce vomiting - Immediately contact physician with urgency.**Section VII - Precautions for Safe Handling and Use****Steps to Be Taken in Case Material is Released or Spilled:** Contain all spills. Use inert absorbent material and dispose in proper chemical waste container. Do not introduce material directly into rivers, lakes, streams, etc.**Waste Disposal Method:** Dispose in accordance with Federal, State and Local regulations.**Precautions to Be Taken in Handling and Storing:** When not in use, keep container closed. Store indoors. Keep from freezing.**Other Precautions:** Product becomes slippery when mixed with water. Use caution when walking where product has contacted floor. Dispose of empty drums by re-conditioner.**Section VIII - Control Measures****Respiratory Protection (Specify Type):** Should vapors exceed PEL, wear NIOSH approved dust and organic vapor respirator for the removal of dried product (dust) from surface.

Ventilation	Local Exhaust:	REQUIRED	Special:	NOT APPLICABLE
	Mechanical (General):	Adequate to maintain below PEL	Other:	Open door/window

Protective Gloves: Recommended if exposure is prolonged - Neoprene**Eye Protection:** Goggles recommended when spraying or working on overhead structures or if direct contact evident.**Other Protective Clothing or Equipment:** Work clothes, face shield and cap if contact or splashing likely.**Work/Hygienic Practices:** Wash thoroughly after use and wash work clothes. Water source in work area recommended.

END