MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : ANTI SIEZE COMPOUND

IDENTIFICATION NUMBER: PT-605 DATE PRINTED: 01/03/06

PRODUCT USE/CLASS : ANTI-SIEZE COMPOUND

SUPPLIER: MANUFACTURER:

PRODUCTS/TECHNIQUES, INC.

3271 S. RIVERSIDE AVE.

RIALTO, CA. 92376

PRODUCTS/TECHNIQUES, INC.

3271 S. RIVERSIDE AVE.

RIALTO, CA. 92376

P.O. BOX 760 P.O. BOX 760

BLOOMINGTON, CA. 92316 BLOOMINGTON, CA. 92316 1-909-877-3951 8 am-4:30 pm 1-909-877-3951 8 am-4:30 pm

AFTER HOURS EMERGENCY PHONE: AFTER HOURS EMERGENCY PHONE: 1-800-424-9300 CHEMTREC 1-800-424-9300 CHEMTREC

PREPARER: B. BODEN, PHONE: 909 877-3951, PREPARE DATE: 02/25/99

	SECT	ION 2 - COMPOS	SITION/INFORM	ATION ON INGRED	IENTS	
ITEM		CHEMICAL 1	NAME	CAS N		T/WT % QUAL TO
01 02	SILICONE FLUID MOLYBDENUM DISULFIDE			63148-62-9 1317-33-5		50.0 % 50.0 %
ITEM	AC	EXPOSU GIH TLV-STEL	OS	HA PEL-CEILING	VAPOR PRES mmHg @ 20C	_
01 02	N/A 10 mg/m3	·	N/A 10 mg/m3	N/A N/AV	N.E. N.E.	N.E. N.E.
(See	Section 16	for abbreviat	tion legend)			
		SECTION 3	- HAZARDS ID	ENTIFICATION		

*** EMERGENCY OVERVIEW ***: Harmful if inhaled. Harmful if absorbed through skin Harmful if swallowed. May cause allergic skin reaction. May cause allergic respiratory reaction.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Direct contact with the liquid or exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can

(Continued on Page 2)

Preparation Date: 02/25/99

Product: PT-605 Page 2

SECTION 3 - HAZARDS IDENTIFICATION

result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: No hazard in normal industrial use. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: No hazard in normal industrial use. Irritating to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: No Information.

FIRST AID - INGESTION: HAVE M.S.D.S. HAZARDOUS INGREDIENT SECTION (SECT. 2) READILY AVAILABLE FOR EMERGENCY PERSONNEL OR DOCTOR.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 500 F - MOLYBDENUM DISULFIDE

(TAGLIABUE CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N/E

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire).

(Continued on Page 3)

Preparation Date: 02/25/99 Page 3

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

RESPIRATORY PROTECTION:

Product: PT-605

All individual company safety policies should be reviewed. If a company determines that threshold limit values and air quality contaminant levels have not been exceeded, then that company should set it's own policies regarding the use of respirators. Always follow all local, state, and federal laws and regulations regarding the use of respirators.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: No Information.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 400 - 400 F VAPOR DENSITY : Is heavier than air

VAPUR DENOTITION ODOR THRESHOLD : N/E : PUNGENT ODOR ODOR

(Continued on Page 4)

Product: PT-605 Preparation Date: 02/25/99 Page 4

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

: GRAY LIQUID/PASTEEVAPORATION RATE: Is slower than Butyl APPEARANCE

SOLUBILITY IN H2O: NONE Acetate

SPECIFIC GRAVITY: 1.6142 FREEZE POINT : N/E pH @ 0.0 % : N/E VAPOR PRESSURE : N/E

PHYSICAL STATE : LIQUID VISCOSITY

COEFFICIENT OF WATER/OIL DISTRIBUTION: N/E

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No Information.

INCOMPATIBILITY: (Materials to avoid):

strong acids and bases, oxidizers, and selected amines.

HAZARDOUS DECOMPOSITION PRODUCTS: CO and CO2. Other unknown hazardous

products are possible.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state, and

federal regulations.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: THIS MATERIAL IS NOT REGULATED PER DOT

DOT TECHNICAL NAME: N/A

DOT HAZARD CLASS: N/A HAZARD SUBCLASS: N/A

DOT UN/NA NUMBER: N/A PACKING GROUP: N/A RESP. GUIDE PAGE:

(Continued on Page 5)

Page 5

SECTION 14 - TRANSPORTATION INFORMATION

SECTION 15 - REGULATORY INFORMATION

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % No non-hazardous components exist

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

Product: PT-605

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

The chemical substances in this product are on the TSCA Section 8 Inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER No information is available.

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME ----- CAS NUMBER
No non-hazardous materials are among the top five ingredients.

Product: PT-605 Preparation Date: 02/25/99 Page 6

SECTION 15 - REGULATORY INFORMATION

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER

No non-hazardous ingredients are present at greater than 3%.

CALIFORNIA PROPOSITION 65:

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 11/05/98

REASON FOR REVISION: NEW COMPUTER SYSTEM

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.00 lbs/gal, 0 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,

N.D. - Not Determined

The information in this document is believed to be correct as of the date printed. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

<END OF MSDS>