

09-00985

The Valspar Corporation

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Material Identification

Product ID: 069.00A1100.076
Product Name: A1100 GLOSS BLACK 6U
Product Use: Paint product.
Print date: 14/Dec/2005
Revision Date: 10/Dec/2005

Company Identification

The Valspar Corporation - Architectural Coatings Division
 1000 Lake Road
 Medina, OH 44256
Manufacturer's Phone: 1-330-725-4511

24-Hour Medical Emergency Phone: 1-888-345-5732

2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Common Name CAS-No. | Approx. Weight % | Chemical name |
|--|---------------------|------------------------------|
| DIMETHYL KETONE 67-64-1 | 40 - 45 | ACETONE |
| PROPANE 74-98-6 | 15 - 20 | Propane |
| XYLENE (W/ ANTI-STATIC) 1330-20-7 | 5 - 10 | Xylenes (o-, m-, p- isomers) |
| BUTANE 106-97-8 | 5 - 10 | Butane |
| ETHYL 3- ETHOXYPROPIONATE 763-69-9 | 1 - 5 | Ethyl 3-ethoxypropionate |
| ETHYL ACETATE 141-78-6 | 1 - 5 | Ethylacetate |
| ETHYLBENZENE 100-41-4 | 1 - 5 | Ethyl benzene |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | Methyl ethyl ketone |
| PROPRIETARY RESIN | 1 - 5 | PROPRIETARY RESIN |
| CARBON BLACK 1333-86-4 | .1 - 1 | CARBON BLACK |

If this section is blank there are no hazardous components per OSHA guidelines.

3. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
 Ingestion
 Skin absorption

Product ID: 069.00A1100.076

Emergency Overview:

This section not in use.

This product contains ingredients that may contribute to the following potential acute health effects:

Inhalation Effects:

Harmful if inhaled. May affect the brain, nervous system, or respiratory system, causing dizziness, headache, nausea or respiratory irritation.

Eye Contact:

Causes eye irritation.

Skin Contact:

May cause moderate skin irritation.

Acute Ingestion:

None known

Other Effects:

May cause kidney damage. May cause liver damage.

This product contains ingredients that may contribute to the following potential chronic health effects:

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged and/or repeated contact can result in skin irritation. May cause skin drying with prolonged exposure. Possible cancer hazard. Contains ingredients which may cause cancer based on animal data. Risk of cancer depends on duration and level of exposure.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

4. FIRST AID MEASURES**Inhalation:**

If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention.

Eye Contact:

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Skin Contact:

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes.

Ingestion:

If swallowed, contact medical personnel immediately to determine best course of action.

Medical conditions aggravated by exposure: Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|---------------------------|---------------------------|
| Flash point (Fahrenheit): | -31° F (-35° C) TCC/PM |
| Lower explosive limit: | 2 % |
| Upper explosive limit: | 13 % |
| Autoignition temperature: | Not available. ° F (° C) |
| Sensitivity to impact: | No. |

Sensitivity to static discharge:

Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
See Section 10.

Hazardous combustion products:

Unusual fire and explosion hazards:

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers until disposed of in compliance with applicable regulations. Contains oxidizable materials.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Use water spray to cool nearby containers and structures exposed to fire. Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate area. Avoid breathing of vapors. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 5, "Unusual Fire and Explosion Hazards", for proper container and storage procedures. Remove sources of ignition. Remove with inert absorbent and non sparking tools. Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks, and flames. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

Skin protection:

Appropriate chemical resistant gloves should be worn. To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Required when spraying or applying in confined area. Ventilation equipment should be explosion proof. Eliminate ignition sources.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

| Common Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|--------------------------------------|---------------------|---------------------------------|-------------------------|-------------------|
| DIMETHYL KETONE 67-64-1 | 40 - 45 | 2400 mg/m ³ 1000 ppm | | |
| PROPANE 74-98-6 | 15 - 20 | 1800 mg/m ³ 1000 ppm | | |
| XYLENE (W/ ANTI-STATIC) 1330-20-7 | 5 - 10 | 435 mg/m ³ 100 ppm | | |
| ETHYL ACETATE 141-78-6 | 1 - 5 | 1400 mg/m ³ 400 ppm | | |
| ETHYLBENZENE 100-41-4 | 1 - 5 | 435 mg/m ³ 100 ppm | | |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | 590 mg/m ³ 200 ppm | | |
| CARBON BLACK 1333-86-4 | .1 - 1 | 3.5 mg/m ³ | | |

ACGIH Threshold Limit Value (TLV's)

| Common Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|--------------------------------------|---------------------|-----------------------|---------|----------------|-------------------|
| DIMETHYL KETONE 67-64-1 | 40 - 45 | 500 ppm | 750 ppm | | |
| PROPANE 74-98-6 | 15 - 20 | 1000 ppm | | | |
| XYLENE (W/ ANTI-STATIC) 1330-20-7 | 5 - 10 | 100 ppm | 150 ppm | | |
| BUTANE 106-97-8 | 5 - 10 | 1000 ppm | | | |
| ETHYL ACETATE 141-78-6 | 1 - 5 | 400 ppm | | | |
| ETHYLBENZENE 100-41-4 | 1 - 5 | 100 ppm | 125 ppm | | |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | 200 ppm | 300 ppm | | |
| CARBON BLACK 1333-86-4 | .1 - 1 | 3.5 mg/m ³ | | | |

If this section is blank, no information is available.

9. PHYSICAL PROPERTIES

| | |
|---|--------------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | Liquid |
| pH: | Not determined. |
| Vapor pressure: | NOT DETERMINED mmHG @ 68° F (20° C) |
| Vapor density (air = 1.0): | 5 |
| Boiling point: | -42° F (-41° C) |
| Solubility in water: | Not determined. |
| Coefficient of water/oil distribution: | Not determined. |
| Density (lbs per US gallon): | 6.29 |
| Specific Gravity | .75 |
| Evaporation rate (butyl acetate = 1.0): | 5.6 |

10. STABILITY AND REACTIVITY

Stability

Conditions to Avoid:

Incompatibility:

Hazardous Polymerization:

Hazardous Decomposition Products:

Stable

None known.

Strong oxidizers.

None anticipated.

Carbon monoxide and carbon dioxide.

Sensitivity to static discharge:

Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

Mutagens:

Teratogens:

Carcinogens:

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans.

| Common Name CAS-No. | Approx. Weight % | IARC Group 1 - Human Evidence | IARC Group 2A - limited human data | IARC Group 2b - sufficient animal data |
|---------------------------|---------------------|----------------------------------|---------------------------------------|---|
| ETHYLBENZENE 100-41-4 | 1 - 5 | | | Monograph 77, 2000 |
| CARBON BLACK 1333-86-4 | 1 - 1 | | | Monograph 65, 1996 |

| Common Name CAS-No. | Approx. Weight % | NTP Known carcinogens | NTP Suspect carcinogens | NTP Evidence of carcinogenicity |
|--------------------------|---------------------|--------------------------|----------------------------|--|
| ETHYLBENZENE 100-41-4 | 1 - 5 | | | male rat-clear evidence; female rat-some evidence; male mice- some evidence; female mice-some evidence |

| Common Name CAS-No. | Approx. Weight % | OSHA Select carcinogens | OSHA Possible select carcinogens | ACGIH Carcinogens |
|--------------------------|---------------------|----------------------------|-------------------------------------|---|
| ETHYLBENZENE 100-41-4 | 1 - 5 | | | Group A3 Confirmed animal carcinogen with unknown relevance to humans. |

If this section is blank, no information is available.

12. ECOLOGICAL DATA

Not available at this time.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: CONSUMER COMMODITY ORM-D
UN ID Number: CONCOM

49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

International Air Transport Association:

Proper Shipping Name: AEROSOLS, FLAMMABLE
Hazard Class: 2.1
UN ID Number: UN1950

International Maritime Organization:

Proper Shipping Name: AEROSOLS
Hazard Class: 2
UN ID Number: UN1950

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

| Common Name CAS-No. | Approx. Weight % | SARA 302 | SARA 313 | CERCLA RQ IN LBS. |
|--------------------------------------|---------------------|----------|---|-------------------|
| DIMETHYL KETONE 67-64-1 | 40 - 45 | | | 5000 |
| XYLENE (W/ ANTI-STATIC) 1330-20-7 | 5 - 10 | | form R reporting required for 1.0% de minimis concentration | 100 |
| ETHYL ACETATE 141-78-6 | 1 - 5 | | | 5000 |
| ETHYLBENZENE 100-41-4 | 1 - 5 | | form R reporting required for 1.0% de minimis concentration | 1000 |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | | | 5000 |

SARA 311/312 Hazard Class:

Acute: Yes
Chronic: Yes
Flammability: Yes
Reactivity: No
Sudden Pressure: Yes

U.S. STATE REGULATIONS:

Pennsylvania Right To Know:

| | |
|--------------------------|--------------|
| PROPRIETARY RESIN | Trade Secret |
| XYLENE (W/ ANTI-STATIC) | 1330-20-7 |
| ETHYL ACETATE | 141-78-6 |
| BUTANE | 106-97-8 |
| ETHYLBENZENE | 100-41-4 |
| PROPANE | 74-98-6 |
| ETHYL 3-ETHOXYPROPIONATE | 763-69-9 |
| METHYL ETHYL KETONE | 78-93-3 |
| DIMETHYL KETONE | 67-64-1 |

Additional Non-Hazardous Materials

| | |
|-------------------|--------------|
| PROPRIETARY RESIN | Trade Secret |
|-------------------|--------------|

California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer.

Rule 66 status of product

Photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories**TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

Not all components in this product are listed on the Domestic Substances List.

16. OTHER INFORMATION**HMIS Codes**

| | |
|----------------------|--|
| Health: | 2 |
| Flammability: | 4 |
| Reactivity: | 1 |
| PPE: | X - See Section 8 for Personal Protective Equipment (PPE). |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.